



Portable work light

A quality product for professionals.



Description	ATEX certified LED portable work light. Standard provided with 10m. cable. To be used for inspection- , maintenance- cleaning- , and construction work in explosion hazardous areas. Unique 2p or 3p connecting possibility.
Enclosure	Antistatic polypropylene. Stainless steel components.
Diffuser	Maintenance free tempered glass, equipped with protective film.
Dimensions	388 x 319 x 147 mm.
Weight	4,5 kg.
Light source	81 LEDs behind an eye friendly opaque filter. 5000K Safe light according to IEC 62471
Light output	4100 lumen
Power	35W
Power supply	Full range 24VAC/DC - 42VAC/DC - 48VAC/DC
Standard cable	10m. H07RN-F cable 2 x 2.5mm ² , optional plug (ATX or CEAG).
Certification	II 2G Ex ib mb IIC T4 Gb II 2D Ex ib mb T135°C Db
Atex zones	Suitable for zone 1, 2, 21 and 22.
Ambient temp.	-20 °C to + 50 °C
IP:	Depending of optional socket. Without socket: the lamp will float (IP65).
Product numbers	6663100 ... (42V) 6763100... (24V), suffix depending on plug.
Certificate	KIWA 19ATEX0039 X
Optional socket	Make ATX or CEAG, 24V/42V, 2p or 3p. Well protected by design of enclosure.
Manufacturing	Designed and produced in the EU.
Accessories	<ul style="list-style-type: none"> • Magnet set (P/N 6920356) • Tripod 1.38 m. t/m 2.50 m. (P/N 6960416) • Other tripods upon request • Scaffolding hook (P/N 6960420) • Sub frame with cord winding support (P/N 6960430). See picture. • Additional protective film (P/N 6921003)

1/08/2019