The HMi 1302 – Z2













Fully Certified

Certi fied to ATEX, IECEx, AEx (NEC505) Section 18 CSA 22,2 EAC



Light & Slim

Weighing in at just 21.5Kg/ 47.3lbs, the 1301-Z1 is just 150mm/5inches thin



Crisp & Bright Display

A high-bright 1000 nit display in the lightest of enclosures.



Super Fast Processor

The intel core i7 processor works 100% from -40°C to +60°C - no throttling back here.



Precision Engineered

Machined from a single piece of aluminium, this is precision engineering at its finest.



| PRODUCT TYPE | PC Workstation | |
|-----------------------------------|--|---|
| MODEL NO | 1302-Z2 | |
| TYPICAL EX CODE | ATEX/IECExEx nA [ic] IIC T4 Gc (Gc) CSA Class 1 Div 2, AEx Class 1 Zone 2 Ex tc IIIC T135°C Dc | |
| | Projected Capacitive Technology (PCT) - Multi Touch, Glove Friendly | |
| DISPLAY SIZE | 19" | |
| DISPLAY TYPE | Sunlight Viewable Glove-Friendly 1000 nit Capacitive LCD Touchscreen | |
| RESOLUTION | SXGA; 1280 x 1024, wide viewing angle, 24 bit colour | |
| PROCESSOR OPTIONS | Dual Core Atom 1.86GHz | Core i7-3517UE, 1.7GHz (TPM Compliant) |
| OPERATING SYSTEM | Windows 10 Enterprise LTSB, Windows 7 Professional | |
| HDD/SSD OPTIONS | 64GB SSD (standard) + second 64GB SSD (optional) | 64GB SSD (standard) also available 128GB or 256GB SSD + second drive 64, 128, 256GB SSD (optional) |
| RAM | 4GB | 8GB + option to upgrade to 32GB |
| COMM OPTIONS | 2 wired Ethernet port triple speed (10/100/1000Mbits/s) or 1 wired Ethernet port triple speed (10/100/1000Mbits/s) with Fiber Optic Ethernet, Wi-Fi (802.11 b/g/n) | |
| KEYBOARD / MOUSE / TOUCHSCREEN | Intrinsically Safe PS/2 Interface | |
| USB | 2 x USB ports | |
| SERIAL COMMUNICATIONS | One RS232 and one RS422/RS485 | |
| INGRESS PROTECTION | IP66 / NEMA4 and NEMA 4X | |

-40°C to +60°C

26.9lbs / 12.2kg

VESA, Yoke, Panel

-40°C to +85°C (-40°F to +185°F)

W 476mm (18.74") x H 427mm (16.81") x D 90mm (3.54")

Shock: In accordance with BS EN60068-2-27:2009 Vibration: In accordance with BS. EN60068-2-6:2008

Exloc Instruments UK Ltd, Unit 7, Riverside Court, Delph, OL3 5FZ

OPERATING TEMPERATURE

STORAGE TEMP

MAX DIMENSIONS

MOUNTING OPTIONS

SHOCK & VIBRATION

WEIGHT



Tel: 01457 239301 sales@exloc.co.uk