

ADD-ON ZONE 1/21

# IS-RSM3x.1



## APPROVALS



ATEX approval: EX-Zone 1/21  
⊕ II 2G Ex ib IIC T4 Gb  
⊕ II 2D Ex ib IIIC T135°C Db



IECEx approval: EX-Zone 1/21  
Ex ib IIC T4 Gb  
Ex ib IIIC T135°C Db

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

## TECHNICAL FEATURES

	IS-RSM3A.1 (wired)	IS-RSM3B.1 (Bluetooth)
<b>LOUDSPEAKER</b>	>103 dB	
<b>KEYS</b>	Function key left (PTT) Function key red (SOS) Function key up & down Function key round All keys, except volume +/-, can be assigned to a function via the „Button App“	
<b>WEIGHT</b>	205 g (weight without cable)	
<b>DIMENSIONS</b>	104,26 x 64,0 x 32,2 mm (LxWxH)	
<b>BATTERY</b>	2.200 mAh	
<b>MICROPHON</b>	Electret condenser microphone   Omni-Directional   Noise cancelling	
<b>BLUETOOTH STANDARD</b>	5.2 BLE (IS-RSM3B.1)	
<b>TYPE OF PROTECTION</b>	IP68; MIL-STD 810H; operating temperature from -20 to 55°C	
<b>INTERFACES</b>	16-pin ISM connector (IS-RSM3A.1) 8-pin ISM interface round	
<b>DELIVERY ACCESSORIES</b>	Desktop Charger	

## SET CONTENT

IS-RSM3x.1, IS-DCRSM3x.1 (Desktop Charger), i.safe PROTECOR 2.0, Safety instructions

