



# F110-EX FULLY RUGGED TABLET

- 13th Generation Intel<sup>®</sup> Core<sup>™</sup> i5 / i7 Processor
- ATEX & IECEx Zone 2/22 explosive atmosphere certified
  Enhanced enterprise security with optional Intel<sup>®</sup> vPro<sup>®</sup>,
- TPM 2.0, Windows Hello face-authentication 5MP camera, and multi-factor authentication options
- 1,200 nits LumiBond display with Getac sunlight readable technology
- LifeSupport battery swappabletechnology







#### **SPECIFICATIONS**

#### Generation

G7 **Operating System** Windows 11 Pro

Mobile Computing Platform

Intel<sup>®</sup> Core™ i5-1335U Processor Max. 4.6GHz with Intel<sup>®</sup> Turbo Boost Technology - 12 MB Intel<sup>®</sup> Smart Cache

Platform options: Intel<sup>®</sup> Core<sup>™</sup> i5-1345U vPro<sup>®</sup> Enterprise Processor Max, 4.7GHz with Intel<sup>®</sup> Turbo Boost Technology - 12 MB Intel<sup>®</sup> Smart Cache

Intel® Core™ i7-1355U Processor Max. 5.0GHz with Intel® Turbo Boost Technology - 12 MB Intel® Smart Cache

Intel<sup>®</sup> Core<sup>™</sup> i7-1365U vPro<sup>®</sup> Enterprise Processor Max. 5.2GHz with Intel<sup>®</sup> Turbo Boost Technology - 12MB Intel<sup>®</sup> Smart Cache

Graphics Intel<sup>®</sup> UHD Graphics Display

11.6" Wide Viewing Angle TFT LCD FHD (1920 x 1080) 1,200 nits LumiBond display with Getac sunlight readable technology

#### Storage & Memory

8GB DDR5 Optional: 16GB/32GB DDR5

256GB PCIe NVMe SSD Optional: 512GB / 1TB / 2TB PCIe NVMe SSD Keyboard

Power button 4 tablet programmable buttons Pointing Device

#### Touchscreen - Dual mode touchscreen (multi-touch and digitizer)

**Expansion Slot** Optional (top side): 1D/2D imager barcode reader or Serial port + LAN (RJ45)<sup>1</sup> Optional (right side): HF RFID reader or Fingerprint reader<sup>11</sup> Optional (back side): Smart card reader

#### I/O Interface

I/O Internace 5MP webcam x 1<sup>™</sup> 8MP auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 Thunderbolt<sup>™</sup> 4 Type-C x 1 Optional: SIM card slot x 1 (Micro-SIM, 3FF) <sup>±/w</sup> Optional: Windows Hello face-authentication 5MP camera (front-facing) x 1<sup>™</sup>

#### **Communication Interface**

Communication interface Intel® Wi-Fi 6E AX211, 802.11ax Bluetooth (v5.3) ° Optional: 10/100/1000 base-T Ethernet Optional: AG LTE mobile broadband with integrated GPS <sup>k, vi, xiv</sup> Optional: 4G LTE mobile broadband with integrated GPS <sup>k, vi, xiv</sup> Optional: 5G Sub-6 with integrated L1/L5 GPS <sup>(v, vi, xiv</sup> Optional: Dual SIM (Micro-SIM 3FF and e-SIM) <sup>kiv</sup>, xiv

#### Security Feature

TPM 2.0 TPM 2.0 Kensington lock Optional: Intel<sup>®</sup> vPro<sup>®</sup> Technology Optional: HF RFID Reader<sup>#, v#</sup>, or Smart card reader, or Fingerprint reader<sup>#</sup> Optional: Windows Hello face-authentication SMP camera (front-facing)<sup>#</sup> Optional: Absolute Persistence<sup>®</sup>

#### Power

AC adapter (65W, 100-240VAC, 50/60Hz) (11.4V, typical 2680mAh; min. 2640mAh) x 2 Optional: High capacity Li-ion battery (11.1V, typical 4200mAh; min. 4080mAh) x 2

#### Dimension (W x D x H) & Weight

314 x 224 x 25.3mm (12.4" x 8.82" x 0.99") 1.68kg (3.7lbs) <sup>viii</sup>

#### Rugged Feature

MIL-STD-810H certified IP66 certified Vibration & 4ft (1.2m) drop resistant <sup>ix</sup> ATEX & IECEx certified

#### **Environmental Specification**

Temperature \*: - Operating: -21°C to 60°C / -6°F to 140°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing

**Explosion Protection** 

### ATEX/IECEx Zone 2/22 Ex II 3G Ex ic op is IIC T4 Gc Ex II 3D Ex ic op is IIIC T130°C Dc **Pre-installed Software**

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager <sup>si</sup> Getac Driving Safety Utility (trial version) Getac KeyWedge Barcode Reader Utility (trial version) Optional: Absolute Secure Endpoint Optional: Absolute Secure Access

#### **Optional Software**

Getac Driving Safety Utility Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMS) Getac Monitoring Getac VGPS Utility <sup>xii</sup>

#### Accessories

Battery (11.4V, typical 2680mAh; min. 2640mAh) AC adapter (65W, 100-240VAC, 50 / 60Hz) Digitizer pen with tether

#### **Optional:**

Optional: Carry bag Battery (11.4V, typical 2680mAh; min. 2640mAh) High capacity battery (11.1V, typical 4200mAh; min. 4080mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) Spare main storage with canister Screen protection film Hard handle <sup>min</sup> Hard handle <sup>min</sup> Hard handle " Shoulder strap (2-point) Shoulder harness (4-point; handsfree) Rotating hand strap & kickstand

#### Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment environment, which can cause cosuy equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

#### Standard

years Bumper-to-Bumper

## F110-EX FULLY **RUGGED TABLET**

- 1D/2D imager barcode reader and Serial port + LAN (RJ45) are mutually exclusive options. HF RFID reader and fingerprint reader are mutually I.
- II.
  - III.
- HE REID reader and fingerprint reader are mutually exclusive options SMP webcam and optional Windows Hello face-authentication SMP camera (front-facing) are mutually exclusive options. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers. IV.
- providers. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is V
- Support GPS, GLONASS, Galileo, BeiDou and QZSS. Only available in USA, UK, EU, Australia, and New VT
- VII.
- Only available in GGP, GN, EN, EN, Zeland 13.56MHz HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant). Weight and dimensions vary from configurations and optional accessories; optional high-capacity batteries add approx. 6mm (H), 0.24kg. VIII.
- Drop test results vary from configurations and optional ĪΧ accessories.
- Tested by an independent third-party test lab following MIL-STD-810H. Χ. XI Available when barcode reader option is selected.
- XII. Models require either embedded or standalone GPS module.
- XIII. Factory option. Not user swappable.
- XIV. Units with 4G/5G option come with an embedded SIM card slot.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.





Getac (UK) Ltd.

quotation by request.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com www.getac.com/en/ Copyright © 2025 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only,available specification shall be subjected to