

Camera Inspection System

Monitor Specification

Screen Size:	5" TFT LCD screen
Display Resolution:	1280 x 720
Zoom:	3 levels
Power Supply:	5V (VDC)
Battery (integrated):	2500mAh
Working Time (full Charge):	3 hours
Memory:	T-Flash Card
Max. Memory Size:	64GB
Picture Format:	JPEG
Video Format:	1280 x 720HD - MP4
Weight: / Dimensions (mm):	255g / (l) 150 x (d) 20 x (h) 100
Weather Proof Rating:	IP64 for light showers



Camera Specification

Image Sensor:	1/4 Inch JX-H62
Effective Pixels:	1280 x 720
Power Supply:	5V (VDC)
Battery (integrated):	1200mAh
Working Time (full Charge):	3 hours LED OFF / 2 hours LED ON
Weight: / Dimensions:	65g / (l) 60 x (d) 40 x (h) 40
Weather Proof Rating:	IP64 for light showers

5" HD TFT monitor with weather proof casing	3x Zoom function for pin point accuracy	100m Transmission range (Unobstructed)	2x LED Camera mounted with 2 metre range	2.4MHz Encrypted transmission
Weather proof with sun visor	GFSK Modulation mode for concentrated signal	JPEG Image capture	AVI 800 x 480 HD Video	2-3H Integral rechargeable battery

Important note: Charging of the camera and monitor must always be done outside of ATEX zones. Not all items will be certified for use in ATEX Zones.

ATEX ExSight 34ft Telescopic Inspection Pole

Pole Height:	10m/34ft
Material:	High Modulus Carbon Fibre
Retracted Height:	202cm
Weight:	2.2kg
Section:	5



Key Features



Clear close ups



Capture Video and Images



Up to 100m connection (Unobstructed)



USB Playback



5" HD Monitor